

# Tactical Micro Two Man Surveillance Tower

The Tactical Micro Two Man Surveillance Tower is the ideal solution for military and civilian use where high aerial manned observation is required. The Two Man Tower features a climate controlled cab with an unobstructed 360 degree view capable of supporting two security personnel. Four easily deployed outrigger arms provide the tower the ability to securely level itself on uneven terrain and safely operate in winds of up to 40 mph. Unlike other manned towers, the Two Man Surveillance Tower includes an attachable ships ladder to allow easy ingress and egress. Setup of the Two Man Surveillance Tower can be accomplished in under 10 minutes with only a few personnel.

## SPECIFICATIONS

Max Ext. Height (To Table)	15'-9"
Max Collapsed Height (Roof)	11'6"
Max Occupants Allowed	2
Total Capacity Allowed	800 lbs
Gross Trailer Weight	9500 lbs
Generator Model	GL7000-USA-TM
Generator Power	7KW
Operating Voltage	220VAC
Max Operating Current	24A
Fuel	Diesel
Fuel Capacity	7.5 GAL
Run Time (Min Load)	48 HR
Max Hydraulic Pressure	2500 psi
Hydraulic Reservoir Capacity	10 GAL
Max Wind Speed (outriggers deployed)	40 mph
A/C Unit Model	AJEQ12-DCF
Tire Size	ST235/80-R16
Max Tire Pressure	80 psi

## Features:

- Climate Controlled Cab
- Fully raised tower in under 4 minutes
- Unobstructed 360 degree view
- 20 ft seated viewing vantage
- Spring assisted 9 ft camera mast allowing mounting of thermal and day PTZ cameras
- Low vibration 7KW generator power pack which allows surveillance for 48 continuous hours
- Deployable wind speed indicator
- Dual white and red light modes to allow optimal surveillance conditions in day or night

